

WIN 2k3/XP IE 7 Install Blocker

Ab 15. Nov. 2006 soll der neue dt. IE7 per Updateservice verteilt werden. Dies kann zu Komplikationen mit bestehenden Applikationen führen.

Um die Installation von IE 7 per automatischem Update zu verhindern kann folgendes Script ausgeführt werden:

- Beispiel: IE70Blocker.cmd mymachine /B (blocks delivery on machine "mymachine")

- IE70Blocker.cmd /U (unblocks delivery on the local machine)

Speichern als: z.B.: IE70Blocker.cmd

```
@echo off
```

```
Echo MICROSOFT TOOL KIT TO DISABLE DELIVERY OF
```

```
Echo MICROSOFT INTERNET EXPLORER 7
```

```
Echo.
```

```
Echo Copyright (C) Microsoft Corporation. All rights reserved.
```

```
Echo.
```

```
set ProductName=Internet Explorer 7.0
```

```
set REGBlockKey=HKLM\SOFTWARE\Microsoft\Internet Explorer\Setup\7.0
```

```
set REGBlockValue=DoNotAllowIE70
```

```
set RemoteMachine=%1
```

```
if ""=="%1" goto Usage
```

```
if "/"=="%1" goto Usage
```

```
if /H=="%1" goto Usage
```

```
if /B=="%1" goto LocalMachine
```

```
if /U=="%1" goto LocalMachine
```

```
set RemoteMachineName=%1
```

```
set Action=%2
```

```
:Parse
```

```
if /B=="%Action%" goto Block
```

```
if /U=="%Action%" goto Unblock
```

```
goto Usage
```

```
:Block
```

```
Echo Blocking deployment of %ProductName% on %RemoteMachineName%
```

```
REG ADD "\\%RemoteMachine%\%REGBlockKey%" /v %REGBlockValue% /t REG_DWORD /d 1 /f
```

```
goto End
```

```
:UnBlock
```

```
Echo Unblocking deployment of %ProductName% on %RemoteMachineName%
```

```
REG DELETE "\\%RemoteMachine%\%REGBlockKey%" /v %REGBlockValue% /f
```

```
goto End
```

```
:LocalMachine
```

```
set Action=%1
```

```
set RemoteMachine=.
```

```
set RemoteMachineName=the local machine
```

```
goto Parse
```

```
:Usage
```

```
Echo.
```

```
Echo This tool can be used to remotely block or unblock the delivery of
```

```
Echo %ProductName% via Automatic Updates.
```

```
Echo.
```

```
Echo -----  
Echo Usage:  
Echo %0 [machine name] [/B] [/U] [/H]  
REM [machine name] [/B|U|H]  
Echo B = Block %ProductName% deployment  
Echo U = Allow %ProductName% deployment  
Echo H = Help  
Echo.  
Echo To block or unblock installation on the local machine use  
Echo period (". " with no quotes) as the machine name  
Echo.  
Echo Examples:  
Echo %0 mymachine /B (blocks delivery on machine "mymachine")  
Echo.  
Echo %0 /U (unblocks delivery on the local machine)  
Echo -----  
Echo.  
  
:End
```